

## Colorcoat® High Reflect

The optimum reflectivity for an internal liner, maximising daylight and reducing requirements for artificial lighting

Colorcoat® High Reflect is a bespoke liner designed with maximum reflectivity to reduce energy requirements, associated operational costs and CO<sub>2</sub> emissions.

- ≥ 85% reflectance, reducing the amount of energy required to achieve the same level of lighting.
- Significantly reduces CO<sub>2</sub> emissions by 2-3% per year, helping to achieve compliance with tightening regulations.
- Can improve daylight factor by 10%.
- Possible energy savings of up to 12% per annum.
- Smooth 30µm polyester coating.
- Galvanised substrate with Zinc metallic coating or equivalent for very good corrosion resistance.

- High-performance reverse side backing coat specially formulated for use in construction applications providing good adhesion to standard systems.

### Typical payback and savings

Lux	Energy savings (%)	CO <sub>2</sub> reduction (%)	Payback (years)
300	11	3*	9.8
500	12	3*	3.8
1000	12	3*	1.1

Based on 4000m<sup>2</sup> building, daytime operation (Payback for 24 hour operation is ≤ 1.5 years).  
 \*Based on SBEM Calculation under NCM conditions for Part L compliance.



Test building with Colorcoat® PE 15 internal liner and Colorcoat® High Reflect.



Close up showing transition from Colorcoat® PE 15 to Colorcoat® High Reflect.

# Colorcoat® High Reflect

## Colorcoat® reassurance

The Colorcoat® brand provides the recognised mark of quality and expertise from Tata Steel. Encompassing nearly fifty years of innovation, strict testing procedures and manufacturing excellence, Colorcoat® provides a range of pre-finished steel products which have been used on countless projects worldwide.

## Product performance

Colorcoat® High Reflect is carefully manufactured in a controlled process to ensure consistent quality and is suitable for interior roof and wall liner trays, cassette systems and composite panels in dry and unpolluted environments. Foam composite panels should always be stacked liner to liner with Colorcoat® High Reflect until cool.

Colorcoat® High Reflect is not suitable for external applications and to ensure it is fitted in the optimum condition, outdoor storage should be minimised during the construction process.

Colorcoat® High Reflect can be expected to last the life of the building in normal, controlled, dry and unpolluted environments.

Tata Steel has a range of Colorcoat® products suitable for different environments and applications.

## Product statement

A fit for purpose guarantee is available. The actual duration of the guarantee will depend on the environment, geographic location and application.

## Product testing

To ensure the integrity of Colorcoat® products, Tata Steel uses laboratory tests to measure their performance against corrosion, effect of sunlight, chemicals and abrasion. All testing of products is carried out in accredited laboratories to international standards.

## Typical properties

Colorcoat® High Reflect			Test standard
Nominal organic coating thickness	µm	30	EN 13523 - 1
Specular Gloss (60°)	%	25-35	EN 13523 - 2
Resistance to rapid deformation (Reverse impact)	J	> 9	EN 13523 - 5
Paint adhesion (cross hatch)		No pick off	EN 13523 - 6
Flexibility: Minimum bend radius	T	5T (16°C)	EN 13523 - 7
Reflectance (Y value)	%	≥ 85%	
Pencil hardness (Surface marking)		HB - 5H	EN 13523 - 4
Solvent resistance (MEK rubs)		> 100	EN 13523 - 11
Corrosion resistance: Salt spray	hours	500	EN 13523 - 8
Humidity	hours	500	EN 13523 - 25
Fire resistance (Spread of flame)		Class 0	BS 476 Part 7

### General notes

1. The figures contained in this table are typical properties and do not constitute a specification. These figures relate to the topcoat. For details on test methods see [www.colorcoat-online.com](http://www.colorcoat-online.com)

## Contact details

[www.colorcoat-online.com](http://www.colorcoat-online.com)

### Trademarks of Tata Steel UK Limited

Colorcoat is a registered trademark of Tata Steel UK Limited.

Care has been taken to ensure that the contents of this publication are accurate, but Tata Steel Europe Limited and its subsidiaries, (including Tata Steel UK Limited), do not accept responsibility or liability for errors or information that is found to be misleading. Suggestions for, or descriptions of, the end use or application of products or methods of working are for information only and Tata Steel Europe Limited and its subsidiaries accept no liability in respect thereof.

Before using products or services supplied or manufactured by Tata Steel Europe Limited and its subsidiaries, customers should satisfy themselves as to their suitability.